DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D119-646 REV. B
AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D119-646 REV. 1
REF. FAA STC: SR02024SE
REF. EASA STC: 10040294

1.0 PURPOSE

To provide an alternate fastening method to secure the D119-646-XXX skidtubes to the aircraft crosstubes

2.0 INSTALLATION OPTION

The MS21250-05006 Bolts can be replaced with MS21250H05006 and lockwired with MS20995C47 (customer supplied) in accordance with MS33540 or AC 43.13. Refer to Figure 1 of this service instruction for reference. The torque on the MS21250H05006 should be limited to 65-85 in-lbs (7.3-9.6 N-m).

3.0 PROCUREMENT

The DSI 9652-011 Bolt Substitution kit can be procured from DART Aerospace. One kit modifies one skidtube.

QTY -011	PART NUMBER	DESCRIPTION BOLT SUBSTITUTION	
Х	DSI 9652-011		
8	MS21250H05006	BOLT	

Α	NEW IS	SUE		МВ	13.04.26
REV.	D		DESCRIPTION	BY	DATE
DESIGN		1/2	DART AEROSPAC	E US	A, INC
DRAWN	KENT, WA				
CHECKE	ĒD	A.V.	DRAWING NO.		REV. A
MFG. AF	PPR.	NA	DSI 9652	9	SHEET 1 OF 2
APPRO\	/ED	All I	TITLE		SCALE
DE APP	₹.	-#	BOLT SUBSTITUTION		NTS
DATE 13.04.26			COPYRIGHT © 2013 BY DART AEROSPACE USA, INC THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.		




FIGURE 1: BOLT SUBSTITUTION

DESIGN	الم	DART AEROSPACE USA, INC		
DRAWN				
CHECKED	A.R.	DRAWING NO.	REV. A	
MFG. APPR.	N/A	DSI 9652	SHEET 2 OF 2	
APPROVED	**	TITLE	SCALE	
DE APPR.	-#	BOLT SUBSTITUTION	NTS	
DATE 13.0	4.26	COPYRIGHT © 2013 BY DART AEROSPACE USA, INC THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.		